

K SERIES

K60 & K80



Our Kevlar® Series of custom in-wall and in-ceiling speakers are designed for superior sound backed by “bulletproof” durability. Kevlar®, a cutting edge polymer, is the material of choice for highly specialized applications where strength and reliability is critical. Its superior acoustical qualities, when molded into speaker cones, are further enhanced by our custom crafted crossover networks, known for their meticulous detail and component quality. The result is unparalleled sound and performance from this series of superb custom install speakers.

Special Features

- Special Kevlar® cone for superior stability and detail at all power levels
- Custom crafted crossover networks reveal crisp, precise response
- Pivot-mount Titanium dome tweeter for the best performance and placement flexibility
- Automatic Overload Protection Circuit
- Gold-plated binding posts
- Hardware in place for easy wall mount installation
- Designed in the USA
- LIFETIME transferable warranty on parts & labor

Specifications

K 60

K 80

	K 60	K 80
System Type	2-Way, Acoustic Suspension	2-Way, Acoustic Suspension
Component Drivers	1" liquid cooled titanium eyeball tweeter 6 1/2" Kevlar® cone woofer with butyl surround	1" liquid cooled titanium eyeball tweeter 8" Kevlar® cone woofer with butyl surround
Frequency Response	50 – 20 kHz (+/- 3 dB)	40 – 20 kHz (+/- 3 dB)
Crossover Frequency	4 kHz	4 kHz
Recommended Amp Power	20 – 150 Watts RMS per channel	20 – 150 Watts RMS per channel
Sensitivity	87 dB @ 1 Watt/1 Meter (2.83 Volts Pink Noise)	86 dB @ 1 Watt/1 Meter (2.83 Volts Pink Noise)
Nominal Impedance	8 Ohms	8 Ohms
Dimensions	8 3/4" W x 12" H x 3 1/4" D (7 5/8" x 10 7/8" cutout)	10 1/8" W x 14 1/4" H x 3 11/16" D (8 7/8" x 12 3/4" cutout)
Finish	White / Paintable	White / Paintable
Weight	3 1/2 lbs. each	5 lbs. each