



Quantum Plasma Inwall Conversion Kit Installation Instructions:

- Determine where on your wall you would like your Quantum Plasma speaker installed. Make sure there are no studs, ductwork or pipes interfering with your desired mounting location!
- Place the wall cutout template on the wall and draw a line around the inside of the template and mark the four mounting hole locations for the wall mount screws on the wall. Remove the template from the wall and carefully cut the speaker mounting hole in the sheetrock.
- Using the included T20 star wrench, remove the top & bottom end caps from your Quantum Plasma speaker and attach the new top & bottom end caps using the original screws.
- Using the M6 screws, attach the wall mount brackets to your Quantum Plasma's new top & bottom end caps leaving them slightly loose to enable easy pivoting. For standard flush-mount installations use the rear mounting hole in the wall mount bracket. If the Quantum Plasma will be pivoted at a great angle you may prefer to use the front bracket mounting hole so the speaker is slightly further out into the room. In this instance please be sure to move the nylon washers from the rear holes of the wall mount brackets to the front holes.
- Drill a 1/4" diameter hole in your wall at each of the four mounting screw locations and insert a wall anchor into each hole.
- Connect speaker wire to your Quantum Plasma speaker.
- Mount the speaker to the wall by inserting the mounting screws through the holes in the wall mount brackets and screwing them into the four wall anchors until the speaker is secure.
- Insert the decorative trim into the mounting hole until it clicks on to the front of the wall mount brackets and is flush with your wall.

